



6b. INTERNAL WALLS

Beton Wood®

Betonwood and sheeting system on wood structure

Building systems for the realization of internal walls and counter-walls using our cement bonded particle boards and dovetailed sheeting system

Complete system for the realization of walls and counter-walls on metallic structures using our cement bonded particle boards and dovetailed sheeting system. Complete supply: panels and installation accessories

STRATIGRAPHY	DESCRIPTION	QUANTITY m ²	PRICE €/m ²	TOTAL	
1 Wall	Masonry, wood, or X-Lam wall				
2 Wood structure	Wood structure beams				
3 Dovetailed sheeting system Beton metal sheet 16mm	The dovetail Beton metal sheet is a light weight self-supporting galvanized steel reinforcement plate used for the formwork and reinforcement of external and internal walls. This sheet offers an excellent solution for acoustics, fire protection and works well with wall-mounted heating and cooling systems and micro-ventilation systems. It has width 630 mm and variable length from 1220 to 2500 mm. Height 16 mm.			0	
4 Screws NF60	The screw has a special anti-corrosion coating that guarantees a 1,000-hour salt spray resistance. Under-head with very sharp self-sinking fins for a perfect housing of the head flush with the slab. Spoon tip (spoon) with very high perforation capacity.			0	
5 Cement bonded particle boards BetonWood N thicknesses 18/20/22mm	The BetonWood N cement bonded particle boards, with high density (1350 Kg/m ³), made of Portland-type cement conglomerate and debarked Pine wood fiber. These panels have the following thermo-dynamics characteristics: thermal conductivity coefficient $\lambda=0,26$ W/mK, specific heat $c=1,88$ KJ/Kg K, coefficient of resistance to vapor penetration $\mu=22,6$ and reaction to fire class A2-fl-s1, according to the standard EN 13501-1. Available in the following sizes: 870x515 mm, 1012x515 mm, 1025x515 mm, 1200x500 mm, 1220x500 mm. Thicknesses from 18 to 22 mm. Available with stepped, tongue&groove and sharp edges.			0	
6 Glue/skimming layer Beton AR1	Monocomponent cementitious mortar for bonding and smoothing thermal insulation panels and Betontherm system. • 4,0 - 6,0kg/m ² depending on the bonding technique. • 1,35-1,55kg/m ² per mm of thickness as skimming layer			0	
7 Net BetonGlass 360	The net has density 360 g/m ³ and complies with the ETAG004 Guideline for ETICS (External Thermal Insulation Composite System), as certified by IFBT GmbH-MFPA Leipzig GmbH. It is suitable for internal and external armored thermal insulation (suitable for any type of BetonTherm product). 50 m ² rolls.			0	
8 Glue/skimming layer Beton AR1	Monocomponent cementitious mortar for bonding and smoothing thermal insulation panels and Betontherm system. • 4,0 - 6,0kg/m ² depending on the bonding technique. • 1,35-1,55kg/m ² per mm of thickness as skimming layer			0	
		IVA 22%	0	TAXABLE	0
				TOTAL AMOUNT	0

Beton Wood®

The functionality of the system will be covered by a BetonWood guarantee for the characteristics of air tightness, water proofing and isolation of the technological package. The warranty will be documented with the appropriate Certificate and Certificate of Assurance that will be delivered at the end of the work to the DD.LL. from the same layer. The forms are available on the BetonWood website as well as the technical indications, the application matrix and the exclusion clauses.