

6. ROOFS

Roof B Isorel - therm and isorel

Ecological roof systems for thermo-acoustic insulation with Therm wood fiber density 160 kg/m³ and Isorel wood fiber density 230 kg/m³ on matchboarding



Complete dry system for high-displacement thermal roofs with Fibertherm wood fiber insulation panels and high-density Isorel wood fiber panels on matchboarding. Excellent system for thermo-acoustic insulation of roofs.

STRATIGRAPHY	DESCRIPTION	QUANTITY m ²	PRICE €/m ²	AMOUNT	
1	Roof tiles	Roof tiles			
2	Block-tiles battes	Wooden battens to support tiles, parallel to the eaves line and with a pitch related to the roof tile.			
3	Battens for ventilation	Battens perpendicular to the gutter line directly on the insulating panel, the strips will have suitable fastening all'assito adhesion with the underlying wood, the distance of the strips is to be assessed according to the load of its own structure and the external loading actions. Thanks to the air gap, the air enters the eaves and rises to the surface, absorbing most of the heat produced by the sun's rays.			
4	Anti-steam barrier FiberTherm multi UDB	High airtight sealant vapor barrier for renovation solutions. Extreme ease of installation for safe and simple use. It has an integrated adhesive strip to secure joints and can be used as a temporary cover. Size: 1,50 m x 50 m Roll surface: 75m ² Weight approx.160 g/m ²		0	
5	Wood fiber panels Fibertherm Isorel 230 thicknesses 19 mm	The panels are made of wood ber with density $\sigma=230 \text{ Kg/m}^3$, are produced with a wet system, in compliance with EN 13171 and EN 13986 standards under constant quality control. The material is characterized by the following thermodynamic characteristics: thermal conductivity coeff. $\lambda=0,05 \text{ W/mK}$, specific heat $c=2100 \text{ J/Kg K}$, resistance to vapor penetration coeff. $\mu=5$ and reaction to fire class E, according to EN 13501-1 standard. The panel dimensions are ... mm for a thickness of ... mm.		0	
6	Wood fiber panels Fibertherm 160 (2 layers) available thicknesses: 60+60 mm 80+80 mm 100+100 mm	The panels are made of wood ber with density $\delta=160 \text{ Kg/m}^3$, are produced with a wet system, in compliance with EN 13171 and EN 13986 standards under constant quality control. The material is characterized by the following thermodynamic characteristics: coefficient of thermal conductivity $\lambda=0.039 \text{ W/mK}$, specific heat $c=2100 \text{ J/Kg K}$, coefficient of resistance to vapor penetration $\mu=5$ and reaction to fire class E, according to EN 13501-1 standard. The dimensions are ... mm for a thickness of ... mm. The wood comes from forests controlled by FSC reforestation cycles.		0	
7	Steam brake FiberTherm multi membra 5	Steam brake for better airtightness on the outer side of the roof, resistant to UVrays, excellent adhesion properties and tear resistance. Size: 1,50 mx50 m Roll surface: 75m ² Weight approx.110 g/m ²		0	
8	Matchboard	Matchboard thickness of 25 mm			
		TAX IVA 22%	0	TAXABLE	0
				TOTAL AMOUNT	0



The functionality of the system will be covered by a BetonWood guarantee for the characteristics of air tightness, water proofing and isolation of the technological package. The warranty will be documented with the appropriate Certificate and Certificate of Assurance that will be delivered at the end of the work to the DD.LL. from the same layer. The forms are available on the BetonWood website as well as the technical indications, the application matrix and the exclusion clauses.